



型号参数 Specification

型号 Model	功率 Power(kW)	产量 Capacity(t/h)
SZLH380	30	0.3-0.5
SZLH470	55	0.8-1.0
SZLH560	90	1.2-1.5
SZLH760	160	1.5-2.5
SZLH850	220	2.5-3.5

产品优势 Product Advantage

1、垂直进料

垂直进料、直接到位、模具静止、压轮旋转、物料离心、均匀四周。

2、环形模具

双层环形模具、立向结构、利用制粒室散热降温一机两用，更多选择，更多收获。

3、独立的出料装置

独立的出料装置、保证颗粒的成型率、设计合理、低耗高能。24小时工作，全自动润滑。

4、环保节能

主要受力元件采用高合金耐磨材料、易损件寿命是同类产品的两倍。

1, Feeding Vertically

Raw material is feeding vertically and is directly in place, with stationary die and rotary pinch roller, the material is centrifugal and equispaced around the die.

2, Ring Die.

The die is double ring type, with vertical structure. Pelletizing room is also used for cooling, more options, and more gains.

3, Independent ejection device.

The independent ejection device ensures the forming rate of the pellet. The good design lowers the consumption and enhances the efficiency. It works 24 hours and lubricates automatically.

4, Environmental and energy-saving.

The main load-carrying component uses high alloy wear-resistant materials. The wearing parts' lifetime doubles compared with other similar products.