



# Fujian Zhangping CHIQIN Technology Co.,Ltd







Address: No.1292, Donghuan Road, Zhangping City, Fujian Province, China

Email: [tinysu@chiqindrying.com](mailto:tinysu@chiqindrying.com) Mobile: 8615059940392 Website: [www.chiqindrying.com](http://www.chiqindrying.com)



## Products Catalogue

No.	Products Name	Products Photo	Specification	Remarks
1	Conventional Wood Drying Kilns		40m <sup>3</sup> , 50m <sup>3</sup> , 60m <sup>3</sup> , 80m <sup>3</sup> , 100m <sup>3</sup> , 120m <sup>3</sup> , 150m <sup>3</sup> , 200m <sup>3</sup>	Accept Customized, the main material is aluminum alloy
2	Track Type Veneer Drying Kilns		LHG-I: 2.8*22*4(m) LHG-II: 5.2*22*4(m)	the main material is aluminum alloy
3	Heat Pump Drying Kilns		40m <sup>3</sup> , 50m <sup>3</sup> , 60m <sup>3</sup> , 80m <sup>3</sup> , 100m <sup>3</sup> , 120m <sup>3</sup> , 150m <sup>3</sup> , 200m <sup>3</sup>	Accept Customized, the main material is aluminum alloy
4	Fruit And Vegetable Drying Kilns		Customized	Accept Customized, the main material is aluminum alloy
5	Medicinal Material Drying Kilns		Customized	Accept Customized, the main material is aluminum alloy
6	Bamboo Carbonization kilns		2650*1500*1700mm Customized	Accept Customized, the main material is aluminum alloy
7	Bamboo Drying Kiln		Customized	Accept Customized, the main material is aluminum alloy

8	Kiln Fans And Motors		<p>Fan: 80cm, 100cm  Motor: 3hp, 4hp, 5.5hp</p> <p>1. The fan is made of aluminum alloy with accurate die casting, stable in processing and quieter.2. The fan is with resistance high temperature and high moisture protection.3. The fan has the advantage of large air volume, high wind pressure, positive &amp; negative operation.</p>
9	Kiln Radiator		<p>The bimetallic structure radiator adopts the internationally popular aluminum rolled sheet type, which has light weight and low airflow resistance. The base pipe is made of stainless steel, which can resist the steam scouring in the pipe.</p>
10	Kiln Probe And Junction Box		<p>The probe and Junction box are installed in the kiln.They are used to inspect the temperature and moisture inside the kiln.</p>
11	Kiln Moisture Discharging System		<p>Independent control before and after, using special industrial connection, anti-freeze damage. The motor can be turned 0 to 90 degrees based on humidity inside in the kiln</p>
12	Electric Valve System		<p>When the moisture generated in the drying process exceeds the set value,wet motor will open the flap.The moisture is discharged from the positive pressure outlet and fresh air is inhaled from negative pressure import.It finishes the exchange of dry and wet vapor.</p>
13	Control System		<p>CCG-10A automatic drying control systems is latest invention of CHIQIN. the system uses a high-definition LED liquid crystal display touch full screen, which can perform the continuous wood moisture content benchmark in Europe and the United States. The system has multiple fuctions such as power-off memory, abnormal state alarm, etc. and can realize centralized control of multiple sets of equipment through computer to realize remote monitoring and remote service</p>

